



PRODUCT-DETAILS

ACS180-04S-04A8-1

LV AC machinery drive module, IEC: Pn 0.75 kW, 4.8 A, 230 V, UL: Pld 1 Hp, 4.6 A, 230 V (ACS180-04S-04A8-1)



General Information	
Global Commercial Alias	ACS180-04S-04A8-1
Product ID	3AXD50000716586
ABB Type Designation	ACS180-04S-04A8-1
EAN	6438177649151
Catalog Description	LV AC machinery drive module, IEC: Pn 0.75 kW, 4.8 A, 230 V, UL: Pld 1 Hp, 4.6 A, 230 V (ACS180-04S-04A8-1)
Long Description	The ACS180 is a compact and robust adaptable variable speed drive (VSD) for applications such as pumps, fans, compressors, conveyors, winders and mixers. This easy-to-use compact VSD offers excellent performance and quality at superior value with all essential machinery application features embedded. And as a member of ABB's all-compatible drives portfolio, it shares the same architecture and user interfaces for ease of use.

Ordering	
Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS180-04S-04A8-1 PN: 0.75 kW, IN: 4.8 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece

Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	2.028 lb
Product Net Depth / Length	5.630 in
Product Net Height	8.228 in
Product Net Width	2.756 in
Package Level 1 Depth / Length	8.858 in
Package Level 1 Height	4.528 in
Package Level 1 Width	8.661 in
Package Level 1 Units	1 carton

Technical

Number of Phases	1
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Altitude	2000 m
	5 ... 95
Power Factor	0.98
Multiple Battery Information	No battery / cell included
Frequency (f)	47 ... 63 Hz
Frame Size	R0
Input Voltage (U_{in})	200 ... 240 V
Mounting Type	Module
Communication Protocol	MODBUS
Number of Hardware Interfaces	Industrial Ethernet 0 Other 1 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 0
Includes	Control unit
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	4 / 2
Output Current, Normal Use (I_n)	4.8 A
Output Current, Light-Overload Use (I_{LD})	4.6 A
Output Current, Heavy-Duty Use (I_{HD})	3.5 A
Output Power, Normal Use (P_n)	0.75 kW
Output Power, Light-Overload Use (P_{LD})	0.75 kW
Output Power, Heavy-Duty Use (P_{HD})	0.55 kW

Apparent Power Output	1.9 kV·A
Complete Drive Module	
Efficiency (61800-9-2)	

Operating Point Frequency / Current
0/25 %
0/50 %
0/100 %
50/25 %
50/50 %
50/100 %
90/50 %
90/100 %

Technical UL

Output Current, Heavy-Duty Use (UL)	3.7 A
Output Current, Light-Overload Use (UL)	4.6 A
Output Current, Normal Use (UL)	- A
Output Power, Heavy-Duty Use (UL)	0.75 Hp
Output Power, Light-Overload Use (UL)	1 Hp
Output Power, Normal Use (UL)	1 Hp

External Classifications and Standards

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

Additional Information

Product Name	Frequency converter
--------------	---------------------

Categories

Drives → Low Voltage AC Drives → Machinery Drives → ACS180 - Machinery Drive

